



Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
85V	4.5mΩ@10V	100A

Feature

- Split Gate Trench Technology
- Low $R_{DS(ON)}$
- Low Gate Charge
- Low Gate Resistance
- 100% UIS Tested


Application

- Power Switching Application

MARKING:



055NE8N = Device Code
XX = Date Code
Solid Dot = Green Indicator



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain - Source Voltage	V_{DS}	85	V
Gate - Source Voltage	V_{GS}	±20	V
Continuous Drain Current ¹	I_D	100	A
Pulsed Drain Current ²	I_{DM}	400	A
Single Pulsed Avalanche Current ³	I_{AS}	48.5	A
Single Pulsed Avalanche Energy ³	E_{AS}	537.1	mJ
Power Dissipation ⁵	P_D	107.8	W
Thermal Resistance from Junction to Ambient ⁶	$R_{\theta JA}$	60	°C/W
Thermal Resistance from Junction to Case	$R_{\theta JC}$	1.16	°C/W
Junction Temperature	T_J	150	°C
Storage Temperature	T_{STG}	-55~ +150	°C







MOSFET ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain - Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	85			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 80V, V_{GS} = 0V$			1	μA
Gate - Body Leakage Current	I_{GSS}	$V_{GS} = \pm 20V, V_{DS} = 0V$			± 100	nA
On Characteristics⁴						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	2.0	2.9	4.0	V
Drain-source On-resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 50A$		4.5	5.9	m Ω
Forward Transconductance	g_{FS}	$V_{DS} = 5V, I_D = 20A$		57.8		S
Dynamic Characteristics						
Input Capacitance	C_{iss}	$V_{DS} = 42.5V, V_{GS} = 0V, f = 1MHz$		4317		pF
Output Capacitance	C_{oss}			682.3		
Reverse Transfer Capacitance	C_{rss}			29.1		
Gate Resistance	R_g	$V_{DS} = 0V, V_{GS} = 0V, f = 1MHz$		1.7		Ω
Switching Characteristics						
Total Gate Charge	Q_g	$V_{DS} = 40V, V_{GS} = 10V, I_D = 50A$		76.8		nC
Gate-source Charge	Q_{gs}			15.1		
Gate-drain Charge	Q_{gd}			4.8		
Turn-on Delay Time	$t_{d(on)}$	$V_{DD} = 40V, V_{GS} = 10V, R_L = 2.5\Omega$ $R_G = 3\Omega$		16.5		ns
Turn-on Rise Time	t_r			51.8		
Turn-off Delay Time	$t_{d(off)}$			37.1		
Turn-off Fall Time	t_f			8.2		
Source - Drain Diode Characteristics						
Diode Forward Voltage ⁴	V_{SD}	$V_{GS} = 0V, I_S = 50A$			1.4	V

Notes :


- 1.The maximum current rating is limited by package.And device mounted on a large heatsink
- 2.Pulse Test : Pulse Width $\leq 10\mu s$, duty cycle $\leq 1\%$.
- 3.EAS condition: $V_{DD} = 48V, V_{GS} = 10V, L = 0.5mH, R_G = 25\Omega$ Starting $T_J = 25^\circ\text{C}$.
- 4.Pulse Test : Pulse Width $\leq 300\mu s$, duty cycle $\leq 2\%$.
- 5.The power dissipation P_D is limited by $T_{J(MAX)} = 150^\circ\text{C}$.And device mounted on a large heatsink
- 6.Device mounted on $1in^2$ FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^\circ\text{C}$.

Typical Characteristics





PDFN5x6-8L Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.100	0.035	0.043
A1	0.254REF		0.010REF	
A2	0.000	0.050	0.000	0.002
D	4.824	4.976	0.190	0.196
D1	3.910	4.110	0.154	0.162
D2	4.924	5.076	0.194	0.200
E	5.924	6.076	0.233	0.239
E1	3.375	3.575	0.133	0.141
E2	5.674	5.826	0.223	0.229
b	0.350	0.450	0.014	0.018
e	1.270TYP		0.050TYP	
L	0.534	0.686	0.021	0.027
L1	0.424	0.576	0.017	0.023
k	1.190	1.390	0.047	0.055
H	0.549	0.701	0.022	0.028
θ	8°	12°	8°	12°
ϕ	1.100	1.300	0.043	0.051
d	-	0.100	-	0.004